

OLYMPUS, KONICA, MAMIYA 35mm cameras*



OLYMPUS OM-1 50mm f:1.4 or f:1.8 lens

- Mech. speeds from 1 to 1/1000 sec. plus B
- Match needle metering at open aperture

\$334⁰⁰ f:1.8 lens

LENS: Bayonet-mount f:1.8 or f:1.4 Zuiko lens. Focus: 17 in. to infinity. Accepts 49mm filters.

SHUTTER: Cloth focal plane with mechanical speeds from 1/1000 to 1 seconds. Flash synchronization in all speeds to 1/60 sec. Self-timer. VIEWING SYSTEM: View through lens at open aperture. Pentaprism viewfinder. Interchangeable screen.

EXPOSURE CONTROL: Center-weighted Cds match-needle metering. Focus through the lens. CONST.: Film advance lever cocks shutter. Hot shoe socket (shoe sold separately below). Mirror lock-up switch. Interchangeable screen. Vinyl-covered metal body; chrome-look trim. Japan.

ACCESSORIES: Lens cap.
ORDERING INFO: See "C" prefix, p. 28.

Olympus OM-1 with f:1.8 lens.
C3 GA 73211C—Shpg. wt. 3 lbs. \$334.00

Olympus OM-1 with f:1.4 lens.
C3 GA 73212C—Shpg. wt. 3 lbs. \$379.00



(1) 28mm f:3.5 wide angle Zuiko Lens. View angle 75°. Min. focus: 11.8 in. Case, Japan.
C3 GA 73215C—Shpg. wt. 1 lb. \$189.00

(2) 135mm f:2.8 telephoto Zuiko Lens. View angle 18°. Min. focus: 4 ft. 10 3/4 in. Case, Japan.
C3 GA 73216C—Shpg. wt. 1 lb. \$219.00

(3) 75 to 150mm Zoom Zuiko Lens. View angle 32-16°. Min. focus: 5 ft. 2 3/8 in. Case, Japan.
C3 GA 73217C—Shpg. wt. 2 lbs. \$319.00



(4) Camera Case. For Olympus above. Japan.
C3 GA 73213—Shpg. wt. 8 oz. \$27.00

(5) Hot Shoe. For Olympus above. Japan.
C3 GA 73214—Shpg. wt. 1 oz. \$9.50



KONICA Autoreflex N-T3 50mm f:1.4 or f:1.7 lens

- Automatic shutter-preferred system
- Shutter speeds from 1/1000 to 1 sec. plus B
- Cds open-aperture metering

\$379⁰⁰ f:1.7 lens

LENS: 50mm bayonet Hexanon lens. Focus from 17.7 in. to infinity. Accepts 55mm filters.

SHUTTER: Automatic Copal metal focal plane shutter with speeds from 1/1000 second to 1 second. plus B, M, X, M flash sync at 1/1000 sec. X sync from 1 to 1/25 sec. Self-timer.

VIEWING SYSTEM: View through the picture-taking lens. Micro-diaphragm viewfinder. Depth of field preview lever. Manual and automatic indicators, over- under-exposure lights in finder.

EXPOSURE CONTROL: Automatic shutter-preferred exposure system. Cds circuit cells measure specially-weighted area. Manual override.

CONSTRUCTION: Film advance cocks shutter. Meter-circuit/shutter-release lock. Built-in hot shoe. Film, shutter-wind counter. Film box holder. Double exposure provision. Vinyl-covered metal body, chrome-look trim. Japan.

ACCESSORIES: Lens cap.
ORDERING INFO: See "C" prefix, p. 28.

Konica Autoreflex N-T3 with f:1.7 lens.
C3 GA 73003C—Shpg. wt. 3 lbs. \$379.00

Konica Autoreflex N-T3 with f:1.4 lens.
C3 GA 73004C—Shpg. wt. 3 lbs. \$429.00



(6) Case. For Konica above. Strap, Japan.
ORDER INFORMATION: "C" prefix, p. 28.
Shpg. wt. 1 lb. 4 oz. \$19.50
C3 GA 73005

NOTE (1 thru 9): See "C" prefix on page 28



Sekor lenses for Cameras (10) and (11).
(7) 200mm f:3.5 telephoto Lens. View angle 12°. Minimum focus: 7 ft. 6 in. Case, Japan.
C3 GA 73615C—Shpg. wt. 2 lbs. \$109.00
(8) 100mm f:2.8 telephoto Lens. View angle 24°. Minimum focus: 4 ft. Case, Japan.
C3 GA 73614C—Shpg. wt. 1 lb. \$134.00
(9) 35mm f:2.8 wide-angle Lens. View angle 63°. Minimum focus: 1.5 feet. Case, Japan.
C3 GA 73613C—Shpg. wt. 1 lb. \$89.00



(10) MAMIYA DSX 1000 55mm f:1.4 or f:1.8 lens

- Mechanical shutter speeds from 1/1000 to 1 second
- Cds match needle open aperture metering system

\$239⁰⁰ f:1.8 lens

LENS: 55mm Mamiya/Sekor SX f:1.4 or f:1.8 in Pentax thread-type mount. Accepts 52mm filters.

SHUTTER: Cloth focal plane, 1/1000 to 1 sec. FP, X. Flash sync. Self-timer.

VIEWING SYSTEM: View through lens. Central microprism viewfinder. Depth-of-field.

EXPOSURE CONTROL: Dual Cds open aperture through-the-lens metering.

CONSTRUCTION: Film advance lever cocks shutter. Hot shoe. Vinyl-covered metal body; chrome-look trim. Japan.

ACCESSORIES: Case, strap. Lens cap.
ORDERING INFO: See "C" prefix, p. 28.

Mamiya DSX 1000 with f:1.8 lens.
C3 GA 73611C—Shpg. wt. 3 lbs. \$239.00

Mamiya DSX 1000 with f:1.4 lens.
C3 GA 7319C—Shpg. wt. 4 lbs. \$269.00

(11) MAMIYA MSX 1000 55mm f:1.8 lens

- Mechanical shutter speeds from 1/1000 to 1 second
- Open-aperture 10% spot metering

\$229⁰⁰

LENS: Same specifications as f:1.8 above.

SHUTTER: Cloth focal plane shutter with mechanical speeds from 1/1000 to 1 second. FP, X flash synchronization. Self-timer.

VIEWING SYSTEM: View and focus through lens. Central microprism viewfinder. Depth-of-field preview.

EXPOSURE CONTROL: 10% Cds spot metering through the lens at open aperture.

CONSTRUCTION: Film advance cocks shutter. Hot shoe. Vinyl-covered metal body; chrome-look trim. From Japan.

ACCESSORIES: Case, strap. Lens cap.
ORDERING INFORMATION: See "C" prefix, p. 28.

C3 GA 73612C—Shpg. wt. 3 lbs. \$229.00